

# HiLyte Industrial Tower



The new HiLyte Tower has been introduced to our successful Tower and Welded product range, as a result of continuous product research, development and innovation.

The 250mm span frame pitch and double hatchdeck enables users to comply with 3T regulations with ease.

The HiLyte Tower affirms our ongoing commitment to the ever-changing world of Health and Safety in the access equipment industry.

## The HiLyte Tower can offer you:

- 250mm pitch span frame for strength, stability and ease of use.
- New colour coded braces for effortless assembly.
- Smooth and ribbed tubing on braces for quick identification.
- Double hatchdeck for ease of assembly and safe use.
- Choice of toeboards: standard wooden, or new aluminium folding unit\*.
- Fully complies with latest regulations, product standards and requirements - including the 3T method of assembly
- Dual brake on/off system.
- Castings on every rung.
- Quick release.
- Large, articulated rubber feet on all stabilisers.
- Certified to BSEN1004:2004

\*Available Sept 2007.



## QUANTITY SCHEDULE HiLyte Industrial Tower System Single Width to BSEN1004:2004 1.8m 2.5m

Component Schedule	Platform Height	Internal or external work														Internal Only												
		1.2m	1.7m	2.2m	2.7m	3.2m	3.7m	4.2m	4.7m	5.2m	5.7m	6.2m	6.7m	7.2m	7.7m	8.2m	8.7m	9.2m	9.7m	10.2m	10.7m	11.2m	11.7m	12.2m				
150mm Dual Locking Castor		4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
Adjustable Leg		4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
4 Rung Access Frame - HL4SW		-	2	2	-	-	2	2	-	-	2	2	-	-	2	2	-	-	2	2	-	-	2	2	-	-	2	2
6 Rung Access Frame - HL6SW		-	2	-	2	-	2	-	2	-	2	-	2	-	2	-	2	-	2	-	2	-	2	-	2	-	2	-
8 Rung Access Frame - HL8SW		2		2	2	4	2	4	4	6	4	6	6	8	6	8		8	10	8	10	10	12	10	12		12	
Hatch Decks		1	1	1	2	2	2	2	3	3	3	3	4	4	4	4		5	5	5	5	6	6	6	6		6	
Horizontal Brace		6	6	6	10	10	10	10	14	14	14	14	18	18	18	18		22	22	22	22	26	26	26	26		26	
Diagonal Brace		2	4	4	6	6	8	8	10	10	12	12	14	14	16	16		18	18	20	20	22	22	24		24		
Side Toe Board - SW as per deck length		2	2	2	2	2	2	2	2	2	2	2	2	2	2	2		2	2	2	2	2	2	2		2		
End Toe Board - TBESW		2	2	2	2	2	2	2	2	2	2	2	2	2	2	2		2	2	2	2	2	2	2		2		
Standard Stabiliser		-	-	4	4	4	4	4	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-		-		
Telescopic Stabiliser		-	-	-	-	-	-	-	4	4	4	4	-	-	-	-		4	4	4	-	-	-	-		-		
Large Telescopic Stabiliser		-	-	-	-	-	-	-	-	-	-	-	4	4	4	4		-	-	-	4	4	4	4		4		

Components schedule based on 3T specification

## QUANTITY SCHEDULE HiLyte Industrial Tower System Double Width to BSEN1004:2004 1.8m 2.5m

Component Schedule	Platform Height	Internal or external work														Internal Only												
		1.2m	1.7m	2.2m	2.7m	3.2m	3.7m	4.2m	4.7m	5.2m	5.7m	6.2m	6.7m	7.2m	7.7m	8.2m	8.7m	9.2m	9.7m	10.2m	10.7m	11.2m	11.7m	12.2m				
150mm Dual Locking Castor		4	4	4	4	4	4	4	4	4	4	4	4	4	4	4		4	4	4	4	4	4	4		4		
Adjustable Leg		4	4	4	4	4	4	4	4	4	4	4	4	4	4	4		4	4	4	4	4	4	4		4		
4 Rung Access Frame DW - HL4DW		-	2	2	-	-	2	2	-	-	2	2	-	-	2	2	-	-	2	2	-	-	2	2	-	-	2	2
6 Rung Access Frame DW - HL6DW		-	2	-	2	-	2	-	2	-	2	-	2	-	2	-	2	-	2	-	2	-	2	-	2	-	2	-
8 Rung Access Frame DW - HL8DW		2	-	2	2	4	2	4	4	6	4	6	6	8	6	8		8	10	8	10	10	12	10	12		12	
Hatch Decks		1	1	1	2	2	2	2	3	3	3	3	4	4	4	4		5	5	5	5	6	6	6		6		
Standard Deck		1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		1	1	1	1	1	1	1		1		
Horizontal Brace		6	6	6	10	10	10	10	14	14	14	14	18	18	18	18		22	22	22	22	26	26	26		26		
Diagonal Brace		2	4	4	6	6	8	8	10	10	12	12	14	14	16	16		18	18	20	20	22	22	24		24		
Side Toe Board - DW as per deck length		2	2	2	2	2	2	2	2	2	2	2	2	2	2	2		2	2	2	2	2	2	2		2		
End Toe Board - TBEDW		2	2	2	2	2	2	2	2	2	2	2	2	2	2	2		2	2	2	2	2	2	2		2		
Standard Stabiliser		-	-	4	4	4	4	4	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-		-		
Telescopic Stabiliser		-	-	-	-	-	-	-	4	4	4	4	-	-	-	-		4	4	4	-	-	-	-		-		
Large Telescopic Stabiliser		-	-	-	-	-	-	-	-	-	-	-	4	4	4	4		-	-	-	4	4	4	4		4		

### Are you PASMA qualified?

Here at Lyte we have strengthened our commitment to our customers even further with the introduction of access industry training courses. We now offer the nationally recognised PASMA and BLMA courses to all our customers.

The Work at Height Regulations 2005 require that the assembly, dismantling or alteration of Mobile Access Towers should only be undertaken by a competent person, or if being trained, under the supervision of a competent person.

PASMA therefore sponsors training courses provided only by authorised training members. Lyte is proud to be one of these members.

The training courses are based on a format and content agreed by all PASMA members and draws upon their collective, first-hand experience. Widely recognised and recommended by safety professionals, it provides successful delegates who pass a written and practical test with a competency certificate and an encapsulated, credit card-sized Photo card.

### More information

For more information or to book the training course please contact the Lyte Training Coordinator on 01639 846800.